

A	Hinges & pivots
B	Pulls & plates
C	Flush bolts & coordinators
D	Latches, catches & bolts
E	Stops
F2	Exterior hardware
G	Miscellaneous hardware



LG1 Lock guard with security pin

LG7 Lock guard

- LG1 incorporates security frame pin to prevent separation of the door and frame
LG7 does not incorporate the security frame pin
- Ideal for use with mortise or cylindrical locks
- Unit covers the latch bolt area of the door and lock, thereby providing added protection from burglars, vandals or normal abuse
- Non-handed
- Easy installation
- Through bolted with carriage bolts and nuts

Material substrate

- Made from 13 gauge stainless steel, 12 gauge steel (LG1 only) or brass (LG1 only)

Dimensions

- 3" wide x 11-1/2" high
- Bolt center to center: 10-1/2"

Finishes - Steel

BHMA	Description	Substrate	Finish
600*	Primed for paint	Steel	USP
603*	Zinc plated	Steel	US2G
695*	Dark bronze painted	Steel	SP313

Finishes - Brass

BHMA	Description	Substrate	Finish
606*	Satin brass	Brass	US4
612*	Satin bronze	Brass	US10

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory. *Not available on LG7.



LG10 Lock guard

- Ideally suited for use with rose or escutcheon 2-3/4" wide or less
- For use with type 86 mortise and type 161 cylindrical locks (ANSI 156.13 Series 1000 and ANSI 156.2 Series 4000)
- Unique design provides maximum security, virtually eliminating the opening between door and frame at the latch point
- Non-handed
- 2 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel, 12 gauge steel

Dimensions

- 2-1/2" wide x 9-1/2" high
- Stud center to center: 8-1/2"

Available accessory items

- Security pin fasteners

Finishes - Steel

BHMA	Description	Substrate	Finish
600	Primed for paint	Steel	USP

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.



LG11 Lock guard - aluminum doors

- Designed for use on aluminum doors with latch-type locks or doors equipped with electric strikes
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point
- Unit is handed - Specify left or right hand when ordering
- 2 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel, 12 gauge steel

Dimensions

- 3" wide x 9-1/2" high
- Stud center to center: 8-1/2"

Available accessory items

- Security pin fasteners

Finishes - Steel

BHMA	Description	Substrate	Finish
695	Dark bronze painted	Steel	SP313

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.



LG12 Lock guard - narrow

- Narrow design unit for use on rose or escutcheon 3-1/2" or less
- For use with type 86 mortise and type 161 cylinder locks (ANSI 156.13 Series 1000 and ANSI 156.2 Series 4000)
- Unique design provides maximum security, virtually eliminating the opening between door and frame at the latch point
- Non-handed
- 2 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel, 12 gauge steel

Dimensions

- 1-1/2" wide x 9-1/2" high
- Stud center to center: 8-1/2"

Available accessory items

- Security pin fasteners

Finishes - Steel

BHMA	Description	Substrate	Finish
600	Primed for paint	Steel	USP

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.

A Hinges & pivots

B Pulls & plates

C Flush bolts & coordinators

D Latches, catches & bolts

E Stops

F3 Exterior hardware

G Miscellaneous hardware

A	Hinges & pivots
B	Pulls & plates
C	Flush bolts & coordinators
D	Latches, catches & bolts
E	Stops
F4	Exterior hardware
G	Miscellaneous hardware



LG13 Lock guard

- Designed for use on all type 161 cylindrical locks (ANSI 156.2 Series 2000) Monolock and Unilock
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point
- Non-handed
- 2 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel, 12 gauge steel

Dimensions

- 1-1/2" wide x 7" high
- Stud center to center: 4-1/2"

Available accessory items

- Security pin fasteners

Finishes - Steel

BHMA	Description	Substrate	Finish
600	Primed for paint	Steel	USP

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.



LG14 Lock guard - with electric strike

- Narrow design unit for use on rose or escutcheon 3-1/2" or less.
- For use with Von Duprin 6210 and 6211 electric strike.
- No exposed fasteners on face of unit.
- Unique design provides maximum security, virtually eliminating the opening between door and frame at latch point.
- Non-handed
- 4 welded mounting studs. No exposed fasteners on face of unit

Material substrate

- Made from 13 gauge stainless steel

Dimensions

- 2-9/16" wide x 9-1/2" high
- Stud center to center: 8-1/2" and 6-3/4"

Available accessory items

- Security pin fasteners

Finishes - Stainless

BHMA	Description	Substrate	Finish
630	Satin stainless	Stainless steel	US32D

For other colors, consult factory.



U696 One-way viewer - UL

- 150° angle of view
- For doors 1-3/8" to 2-1/16" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation — only a 1/2" hole required
- Suggested installation height: 60" from floor

Material substrate

- Meets ANSI/BHMA A156.16, L23222
- UL listed 90 minute fire doors

Dimensions

- External diameter: 3/4"

Available accessory items

- Trim washer available, 3/4" x .032" thick.
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

Finishes

BHMA	Description	Substrate	Finish
606	Satin brass	Brass	B4
613	Oil rubbed bronze	Brass	B10B
619	Satin nickel	Brass	B15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

For other colors, consult factory.



698 One-way wide angle viewer

U698 One-way wide angle viewer - UL

- 190° angle of view
- 4 optical glass lenses
- For doors 1-3/8" to 2-1/8" thick
- Simple installation — only a 9/16" hole required
- Suggested installation height: 60" from floor

Material substrate

- Meets ANSI/BHMA A156.16, L23222
- U698 is UL listed 90 minute fire doors

Dimensions

- External diameter: 1"
- Lens projects 1/4" from face of door

Available accessory items

- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	B3
619*	Satin nickel	Brass	B15
622*	Matte black	Brass	B-BLK
625*	Bright chrome	Brass	B26
626	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

*For other colors, consult factory. *Not available on 698.*

Hinges & pivots
A

Pulls & plates
B

Flush bolts & coordinators
C

Latches, catches & bolts
D

Stops
E

Exterior hardware
F5

Miscellaneous hardware
G



700 One-way narrow viewer
U700 One-way narrow viewer - UL

- 120° angle of view
- For doors 1-3/8" to 2-1/16" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation—only a 1/2" hole required
- Suggested installation height: 60" from floor

Certifications

- 700 meets ANSI/BHMA A156.16, L23173
- U700 meets ANSI/BHMA A156.16, L23223
- U700 is UL listed 90 minute fire doors

Material substrate

- Made from brass, glass lens

Available accessory items

- Trim washer available, 3/4" x .032" thick.
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

Dimensions

- External diameter: 5/8"

Finishes

BHMA	Description	Substrate	Finish
606	Satin brass	Brass	B4
613*	Oil rubbed bronze	Brass	B10B
619*	Satin nickel	Brass	B15
622*	Matte black	Brass	B-BLK
625*	Bright chrome	Brass	B26
626*	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

For other colors, consult factory. *Not available on 700.



701 One-way narrow viewer for thicker doors
U701 One-way narrow viewer for thicker doors - UL

- 120° angle of view
- For doors 2-1/8" to 2-5/8" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation—only a 1/2" hole required
- Suggested installation height: 60" from floor

Certifications

- 701 meets ANSI/BHMA A156.16, L23173
- U701 meets ANSI/BHMA A156.16, L23223
- U701 is UL listed 90 minute fire doors

Material substrate

- Made from brass, glass lens

Available accessory items

- Trim washer available, 3/4" x .032" thick.
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room

Dimensions

- External diameter: 5/8"

Finishes

BHMA	Description	Substrate	Finish
606	Satin brass	Brass	B4
613*	Oil rubbed bronze	Brass	B10B
619*	Satin nickel	Brass	B15
622*	Matte black	Brass	B-BLK
625*	Bright chrome	Brass	B26
626*	Satin chrome	Brass	B26D
---	Aged bronze	Brass	B-643e/716

For other colors, consult factory. *Not available on 700.